PROFORT FIXED GUARDRAIL

The most have for professionals



5-step model







Can be used against Ø 100 mm wheels a wall

Integrated tool-tray







Evolution of guardrail locking system

► Solid guardrail.

- ▶ Stabilizers with a patented millimetric adjustment system.
- ▶ The rear stand has been designed for working above obstacles (except for 2-step model).
- Non-slip 490 x 400 mm platform with integrated toe boards (height: 100 mm).
- ▶ Ribbed non-slip steps crimped in place (width: 60 mm).
- ► Compact and lightweight.

Product characteristics					
Use	Intensive				
Type of floor	Flat floor				
Max work / access height (m)	3,15				
Material	Aluminium				
Maximum load (kg)	150				
Warranty (years)	5				
Standard	PIRL NFP 93353				
Decree	2004//924				

 $Delivered \ in \ shrink \ film \ with \ POS \ brochure. \ The \ platform \ is \ counted \ as \ a \ step. \ Models \ O2272512 \ and \ O2272513 \ do \ not \ have \ stabilizers.$

Ref.	Folded H (m)	Platform H	Nb of rungs/steps	Weight (kg)	Max access / work H (m)	EAN barcode
02272512	1,73	0,51	2	11,4	2,51	3178740099688
02272513	1,92	0,7	3	13,4	2,7	3178740099718
02272514	2,18	0,93	4	15,8	2,93	3178740099749
02272515	2,43	1,15	5	16,8	3,15	3178740099770



