

# EVOKLIP

## The modular ladder of the roofer

The new roof ladder EVOKLIP has been developed with roofers for 2 years. Much more comfortable, reliable and stable, it meets the requirements of the height's craftsmen.



- ▶ 3 complete packs : 4 ladders + 1 ridge hook
- ▶ 3 types of ladder (250, 330 or 390 mm distance between rungs) to adapt to different shapes of tiles and inclination of the slope
- ▶ Non-slip strips for a secure climbing
- ▶ Reinforced uprights to ensure rigidity and stability in all situations
- ▶ 30% lightest than a classic aluminium ladder
- ▶ Easy set-up
- ▶ Quick climbing with the wide distance between rungs and comfortable with their bevelled shapes

### Product characteristics

<b>Use</b>	Intensive
<b>Type of floor</b>	Roof
<b>Max access / working height (m)</b>	7,42
<b>Material</b>	Aluminium
<b>Maximum load (kg)</b>	150
<b>Warranty (years)</b>	5
<b>Standard</b>	Not covered by European standards



Ridge hook (aluminium single-element). Adaptable with any type of roof



Real steps for secure climbing and bevelled rungs for maximum comfort of the knees



Locking system of the ladders with captive pins



Optional tool-tray with adjustment of the inclination, anti-fall edges and locking system



Reinforced uprights (41 x 26 mm) and rungs (35 x 22 mm) for long life



Optional Ø125 mm wheels with soft covering for quick set up on roofs



Non-slip rubber strips to protect the roof and ensure greater grip



Easy transport at the bottom of the vehicle and on the roof rack. Very compact in folded position

Ref.	Spacing (mm)	Overall H	Weight (kg)	W. (without stab)	Max access / work H (m)	EAN barcode
02453401	250	1,589	4,6	0,4	1,589	3178740192778
02453402	330	1,739	4,4	0,4	1,739	3178740192785
02453403	390	1,649	3,9	0,4	1,649	3178740192792
02453725	250	6,1	23,2	0,4	6,1	3178740192808
02453733	330	6,7	22,4	0,4	6,7	3178740192815
02453739	390	6,3	20	0,4	6,3	3178740192822