


PLATINIUM 500 3-SECTION ROPE-OPERATED

The ultimate in really long ladders

The Platinum 500 Agrip aluminium ladder has 3 sections and a rope-operated extension system for access to heights of up to 14.65 metres. Its rotating pads, adjustable stabilising base, reinforced uprights and angled rungs make this the highest-quality ladder on the market. It complies with the EN 131-6 standard and decree 96-333. It has the NF, GS and VGS quality labels. Quite simply, it offers altitude with total security.



- : These models are very popular for roofing and billposting works.
- : The uprights' ribbed profile offers a secure grip for hands and makes erection even easier.
- : The 25 mm distance between rungs provides optimum comfort both when climbing and coming down the ladder
- : When the sections are deployed, rungs are in line and form a real step under the user's feet



Runners in polyamide



Highly-strength rungs with triple crimp-fitting onto the uprights



Oversized uprights for increased stability



Interchangeable non-slip shoes



Easy deployment thanks to the rope-operated system Automatic extruded aluminium locking pivot with polyamide insert. Replacement required in our works



Product characteristics	
Use	Ultra intensive
Use	Flat floor
Max access / working height (m)	14,65
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Folded H (m)	Deployed Height (m)	Nb of steps	Weight	Width stabilizaters deployed (m)	Section	Max access Height (m)	Gencod
02533311	3	7	3x11	30	1,35	76	7,9	3178740162818
02533313	3,5	8,5	3x13	33,5	1,35	76	9,4	3178740162825
02533316	4,25	9,75	3x16	43,5	1,35	76/91/76	10,65	3178740162832
02533318	4,75	11,24	3x18	47,5	1,35	90/91/90	12,14	3178740162849
02533320	5,25	12,75	3x20	56,5	1,35	90/103/90	13,65	3178740162856
02533322	5,75	13,75	3x22	64,5	1,35	101/103/101	14,65	3178740162863