

SINGLE INSULATED

Electricians key asset

This mixed aluminium/fibreglass ladder complies with the EN 50528, EN 61478 and EN 131 standards, decree 96333 and the NF and GS quality labels. It protects against electrical risks and offers perfect stability thanks to its wraparound pads.



- : Fibreglass uprights to provide protection against electric shocks up to 1, volts.
- : Very lightweight product with aluminium rungs.
- : Very easy to handle, simple and quick to set up.
- : Ribbed non-slip footpads: -3. m models
- : Additional base with reinforced footpads: Additional base with reinforced footpads

Wide base for increased stability (+3. m models)

High-security covering footpads (-3. m models)

30 x 30 mm rungs

Product characteristics	
Use	Ultra intensive
Use	Flat floor
Max access / working height (m)	5,93
Material	FIBER GLASS
Maximum load (kg)	150
Warranty (years)	3
Norms	EN 131, EN 50528
Decree	96333
NF Label //	

Ref.	Deployed Height (m)	Nb of steps	Width stabilizers folded (m)	Width stabilizers deployed (m)	Section	Max access Height (m)	Gencod
04310108	2,41	8	0,36	-	66	3,31	3178740185640
04310110	2,97	10	0,36	-	66	3,87	3178740185657
04310112	3,63	12	0,36	0,81	66	4,53	3178740185664
04310114	4,19	14	0,36	0,81	66	5,09	3178740185671
04310117	5,03	17	0,36	0,91	66	5,93	3178740185688