

# DOUBLE FLARED BASE

## HIGH-PERFORMANCE UNIT

The Dobble aluminium splayed ladder is available with 2x5 to 2x10 steps and provides access to a height of up to 3m31. It is supplied with bucket hooks and retaining straps. It complies with the EN 131 standard and Decree 96-333, and is also NF certified.



- ▶ Perfect stability thanks to its high-security footpads.
- ▶ Anti-pinch safety system.
- ▶ Retaining strap.

### Product characteristics

<b>Use</b>	Highly intensive
<b>Type of floor</b>	Flat floor
<b>Max access / working height (m)</b>	3,31
<b>Material</b>	Aluminium
<b>Maximum load (kg)</b>	150
<b>Warranty (years)</b>	5
<b>Standard</b>	EN 131
<b>Decree</b>	96333
<b>Classe</b>	Professional



Bucket hook



Non-slip 8 mm steps



High-security covering footpads with wear indicator

Ref.	Folded H (m)	Nb of rungs/steps	Weight (kg)	Product width at the base (m)	Wheelbase (m)	Section	Max access / work H (m)	EAN barcode
02255005	1,25	2x5	7,5	0,48	1,19	76	2,15	3178740019853
02255006	1,48	2x6	8,9	0,51	1,38	76	2,38	3178740019860
02255008	1,95	2x8	11,7	0,56	1,75	76	2,85	3178740019877
02255010	2,41	2x10	14,6	0,61	2,13	76	3,31	3178740019945