

PRONOR 3-SECTION COMBINATION

Highly-versatile

The Pronor aluminium 3-way combination ladder has cast aluminium articulations, a splayed base and a steel retaining arm. They guarantee reliability and comfort for all users. Models with 3x8 to 3x12 rungs provide access to heights of up to 8.86 metres and 4 positions. It complies with the EN 131 standard, decree 96-333 and the NF, VGS and GS quality labels.



- ⋮ The most versatile model in the Pronor range.
- ⋮ Extremely rigid with a reinforced ribbed hinge in cast aluminium and a rigid retaining bar.
- ⋮ Lightweight and easy to erect and transport.
- ⋮ 3rd section non-detachable for the +3. m model



For working on flat and uneven surfaces and stairways



Interlocking hooks and ribbed non-slip footpads



Highly-strength rungs with triple crimp-fitting onto the uprights



Models with base and reinforced footpads on request

Product characteristics	
Use	Intensive
Use	Flat and uneven floor
Max access / working height (m)	8,86
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Folded H (m)	Deployed Height (m)	Nb of steps	Weight	Width stabilizers folded (m)	Wheelbase	Section	Max access Height (m)	Gencod
01253012	3,45	7,93	3x12	25,2	118	2,44	79/90/79	8,86	3178740187293
01253008	2,33	5,13	3x8	14,6	0,92	1,53	79,5	6,05	3178740187262
01253009	2,61	5,97	3x9	19,2	1	1,81	79,5	6,9	3178740187279
01253010	2,99	6,81	3x10	21,4	1,09	1,94	79,5	7,74	3178740187286