

PLATINIUM SINGLE

The essential ladder for finishing work



This Platinum aluminium single ladder is available in models ranging from 6 to 24 rungs for access to heights of up to 7.8 metres. Its wraparound pads and reinforced uprights guarantee strength and stability. It complies with the EN 131 standard and decree 96-333 and has the NF quality label.



- Reliable and robust, very easy to handle.
- Reinforced upright profiles with 3 x 3 mm rungs.
- +3m models : Additional base with reinforced footpads



Optional retaining bar
(ref. 9612)



Ladders with hooks
available on request



Highly-strength rungs
with triple crimp-fitting
onto the uprights

Product characteristics

Use	Ultra intensive
Use	Flat floor
Max access / working height (m)	7,8
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Deployed Height (m)	Support H (m)	Wall gap	Nb of steps	Weight	Width stabilizers deployed (m)	Wheelbase	Section	Max access Height (m)	Gencod
02410206	1,85	1,72	0,69	6	3,2	-	0,36	66	2,75	3178740005429
02410207	2,13	1,97	0,8	7	3,7	-	0,36	66	3,03	3178740185305
02410208	2,41	2,23	0,9	8	4,1	-	0,36	66	3,31	3178740185312
02410210	2,97	2,75	1,11	10	5	-	0,36	66	3,87	3178740185329
02410212	3,56	3,27	1,32	12	6,2	0,81	0,36	66	4,43	3178740162207
02410214	4,12	3,79	1,53	14	7,5	0,91	0,43	66	4,99	3178740162214
02410216	4,68	4,31	1,74	16	8,4	0,91	0,43	66	5,55	3178740162221
02410217	4,96	4,57	1,85	17	9,7	1,01	0,43	79,5	5,84	3178740162238
02410218	5,24	4,83	1,95	18	10,3	1,01	0,43	79,5	6,11	3178740162245
02410220	5,8	5,35	2,16	20	11,3	1,11	0,43	79,5	6,67	3178740162252
02410224	6,92	6,39	2,58	24	13,4	1,11	0,43	79,5	7,8	3178740162269