


COMPACT FIBERGLASS


The best for professionals with insulation protection



- : Ribbed non-slip 80 mm steps.
- : 250 x 250 mm platform.
- : Non-jamming aluminium hinges.
- : Rear stand wider than the climbing section for increased stability.
- : Rear stand wider than the climbing section for increased stability.



Tool holder with screw tray



Automatic anti-lift lock on the platform



Crimped connection without screws and rivets. Steps 8 mm wide



Non-slip moulded footpads Ref. 9763

Maximum safety No risk of tipping over forward

Product characteristics	
Use	Intensive
Use	Flat floor
Max access / working height (m)	3,61
Material	FIBER GLASS
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 50528
Decree	96333
Recommendations	Electric Test EN 50528
NF Label //	

Ref.	Folded H (m)	Platform height	Wheelbase	Nb of steps	Weight (kg)	Width (without stab)	Mini requirements EN131	Access / working Height (m)	Gencod
04472003	1,45	0,69	0,43	3	6	0,52	0,41	2,69	3178740027759
04472004	1,7	0,92	0,46	4	7	0,55	0,44	2,92	3178740027766
04472005	1,95	1,15	0,49	5	8	0,57	0,46	3,15	3178740027773
04472006	2,2	1,38	0,51	6	9	0,6	0,49	3,38	3178740027780
04472007	2,45	1,61	0,54	7	11	0,63	0,51	3,61	3178740027797