

COMPACT

The economic model




- : Ribbed non-slip 80 mm steps.
- : 250 x 250 mm platform.
- : Non-jamming aluminium hinges.
- : Flared rear stand : for increased stability and more compact when folded.



Tool-holder with screw tray.



Bucket hook. Max. weight 1 kg



Automatic anti-lift lock on the platform



Reinforced hinge



Non-slip moulded footpads Ref. 9728



Maximum safety No risk of tipping over forward

Product characteristics	
Use	Regular
Use	Flat floor
Max access / working height (m)	3,64
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Folded H (m)	Platform height	Wheelbase	Nb of steps	Weight (kg)	Width (without stab)	Mini requirements EN131	Access / working Height (m)	Gencod
02372303	1,29	0,57	0,65	3	3,6	0,5	0,41	2,57	3178740033880
02372304	1,52	0,78	0,81	4	4,2	0,53	0,44	2,78	3178740033897
02372305	1,75	1	0,96	5	5	0,55	0,46	3	3178740033903
02372306	1,98	1,21	1,11	6	5,8	0,57	0,49	3,21	3178740033910
02372307	2,21	1,42	1,27	7	6,5	0,6	0,51	3,42	3178740033927
02372308	2,44	1,64	1,42	8	7,3	0,63	0,54	3,64	3178740033934