

# SHERPASCOPIC TELESCOPIC

## Optimal comfort on every type of ground

This Tubesca aluminium mobile platform sets the standard for telescopic platforms. Available in several models at heights of up to 4.5 metres with 3-4/4-6/7-9/7-10 steps. Its reinforced uprights, wide platform, adjustable stabilisers and semi-automatic rigid guardrails make the Sherpascopic an extremely robust, stable product. It has a tool carrier, transport wheels and 80 mm steps. It meets the PIR-PIRL standards for mobile platforms, complies with decree 2004-924, standard EN 131-7 and has the NF quality label.



3/4-step model

- ▶ Intuitive high-resistance level offset system.
- ▶ Solid guardrail.
- ▶ Stabilizers with a patented millimetric adjustment system.
- ▶ Non-slip 600 x 420 mm platform with integrated toeboards.
- ▶ Ribbed non-slip rungs crimped in place (30 x 30 mm).
- ▶ Extremely strong handrails.
- ▶ Automatic interlock between the different elements.


Product characteristics	
<b>Use</b>	Highly intensive
<b>Type of floor</b>	Flat and uneven floor
<b>Max access / working height (m)</b>	4,46
<b>Material</b>	Aluminium
<b>Maximum load (kg)</b>	150
<b>Warranty (years)</b>	5
<b>Standard</b>	PIR NFP 93353 ; PIR NFP 93352 ; EN 131-7
<b>Decree</b>	2004//924
<b>NF Label //</b>	



High reliability gate lock




Ø 160 mm wheels



Rear anti-lift locks



Lifting rings



Evolution of guardrail locking system

Delivered in shrink film with POS brochure. The platform is counted as a step. Model 02272250 is certified to be NF PIRL 93353 compliant. Models 02272251 /02272252 and 02272253 are NF PIR 93352 certified.

Ref.	Folded H (m)	Platform H	Wheelbase (m)	Nb of rungs/steps	Weight (kg)	Max access / work H (m)	EAN barcode
02272250	2,13	0,78-1,02	1,39 - 1,57	3-4	23,1	3,02	3178740098698
02272251	2,44	1,07-1,53	1,61 - 1,97	5-7	26,4	3,53	3178740098704
02272252	3,2	1,76-2,23	2,15 - 2,52	8-10	31	4,23	3178740098711
02272253	3,2	1,76-2,46	2,15 - 2,73	8-11	33	4,46	3178740152567