

NEOLIUM 200 BOX


HIGH-PERFORMANCE WELDED ALUMINIUM



- ▶ Advanced guardrail system with diagonals
- ▶ Welded aluminium scaffold, 50 mm uprights and rungs
- ▶ One-piece platform
- ▶ Wheels Ø 200 mm with powerful locking system and millimetric adjustment system
- ▶ Work with level offset.

Product characteristics

Use	Highly intensive
Type of floor	Flat and uneven floor
Max access / working height (m)	14
Material	Aluminium
Max load (kg / m²)	200
Warranty (years)	5
Standard	EN 1004/1
Decree	2004/924



Aluminium toeboards
Ø 150 mm integrated
into the floor



Advanced guardrail
system with diagonals



Anti-slip and swivelling
stabilizers



Wheels Ø 200 mm
adjustable over
175 mm up to 12.5
increments



NF certified product. Certifying organization: AFNOR Certification, 11, rue Francis de Pressensé, F-93571 La Plaine Saint Denis Cedex. Certification reference: NF site equipment (NF096) available on www.marque-nf.com. The NF mark certifies compliance with the EN 1004-1 standard and the NF096 standard.

Ref.	Overall H	Platform H	Nb of platforms	Weight (kg)	W. stabilizers folded (m)	Width stab deployed (m)	W. stabilizers folded (m)	Length stab deployed (m)	Max access / work H (m)	EAN barcode
02921502	3,13	2	1	108	0,92	3,42	2,26	4,66	4	3534740165813
02921504	5,13	4	2	158	0,92	3,42	2,26	4,66	6	3534740165820
02921506	7,13	6	3	209	0,92	3,42	2,26	4,66	8	3534740165837
02921508	9,13	8	4	277	0,92	4,71	2,26	5,9	10	3534740165844
02921510	11,13	10	5	327	0,92	4,71	2,26	5,9	12	3534740165851
02921512	13,13	12	6	379	0,92	4,71	2,26	5,9	14	3534740165868