

NEOLIUM 200 LINE

HIGH-PERFORMANCE WELDED ALUMINIUM



- ▶ Brace version
- ▶ Welded aluminium scaffold, 50 mm uprights and rungs
- ▶ Platform with toeboards apart integrate
- ▶ Wheels Ø 200 mm with powerful locking system and millimetric adjustment system
- ▶ Work with level offset.

Product characteristics

Use	Highly intensive
Type of floor	Flat and uneven floor
Max access / working height (m)	14
Material	Aluminium
Max load (kg / m²)	200
Warranty (years)	5
Standard	EN 1004/1
Decree	2004/924



Removable aluminium toeboards Ø 150 mm for rapid set up



Brace version



Anti-slip and swivelling stabilizers



Wheels Ø 200 mm with powerful locking system and millimetric adjustment system



Ref.	Overall H	Platform H	Nb of platforms	Weight (kg)	W. stabilizers folded (m)	Width stab deployed (m)	W. stabilizers folded (m)	Length stab deployed (m)	Max access / work H (m)	EAN barcode
02921802	3,13	2	1	105	0,92	3,42	2,26	4,66	4	3534740165998
02921804	5,13	4	2	157	0,92	3,42	2,26	4,66	6	3534740166001
02921806	7,13	6	3	207	0,92	3,42	2,26	4,66	8	3534740166018
02921808	9,13	8	4	275	0,92	4,71	2,26	5,9	10	3534740166025
02921810	11,13	10	5	326	0,92	4,71	2,26	5,9	12	3534740166032
02921812	13,13	12	6	377	0,92	4,71	2,26	5,9	14	3534740166049