

NANO'TOWER

The mini-scaffold with maxi-flexibility

Real revolution in the field of mobile scaffolding, the Nano'Tower's assembly/disassembly in complete safety is made in less than 1 minute and can be loaded in the trunk of a small utility car. Easy movement by just one person thanks to its extrem lightness and its aluminium structure (lightweight: 33 kg excluding toeboards). With one product, the user can work on 4 floor levels (max working height: 3,00 m). It complies with the decree 2004-924 and meets the tests requirements of the standard EN 1004.



1,00 m platform use

- ▶ Assembly in less than 1 minute, no screws or tools required for putting it up.
- ▶ Time saving: movement in 1 single element.
- ▶ Small footprint: at ease in a lift. Sizes of the unfolded product: L 0,65 x l 1,18 x H 1,42 m.
- ▶ Free-standing with its wheels system.
- ▶ Assembly/disassembly in complete safety by just one person.
- ▶ Platform sizes: 1,02 x 0,60 m.
- ▶ Access by a trap: safety during climbs and descents in 0,75 and 1,00 m use.
- ▶ Optional transport kit ref. 22406090.

Product characteristics

Use	Intensive
Type of floor	Flat floor
Max access / working height (m)	3,00
Max load (kg / m²)	200
Warranty (years)	5
Standard	Not covered by standards
Decree	2004//924



Easy to handle thanks to its lightness. 33 kg excluding toeboards.



Easy set up: opening in a simple gesture. Folding base with automatic locking.



Integrated platform: low load, 1 only handling. Floor adjustment every 25 cm.



Integrated guardrail: safety induced. Rails and middle-rails only in 0,75 and 1,00 m use.



Ultra mobile: 360° non-marking swivel wheels with brake, Ø 125 mm.



Easy transport: transportable in a light vehicle.

Ref.	Overall H	Platform H	Nb of platforms	Weight (kg)	W. stabilizers deployed (m)	W. stabilizers deployed (m)	Max access / work H (m)	EAN barcode
22406410	2,07	0,25 - 0,50 - 0,75 - 1,00	1	37,00	1,12	1,65	3,00	3178740203559